HANNspree

Experts in **Display**

HL 400 UPB

100,33 cm / 39,5" Diagonal LED Backlight – Format 16:9

- 39,5" 16:9 LED Backlight Monitor
- 1920 x 1080 Full HD Resolution
- 178° / 178° Ultra-Wide Viewing Angle
- 5000:1 High Contrast Ratio
- Video Inputs: HDMI x 2, VGA
- HDMI CEC Function
- Built-In Stereo Speakers 8W + 8W
- Wall-Mountable (VESA)
- USB Media Player
- Auto-Playback (Photo and Video)
- Auto Power-On
- Remote Control



MEDIA PLAYER





100.33 cm / 39.5"

Part No.: HL 400 UPB

SIZE, RESOLUTION



39,5" Size 16:9 Aspect Ratio



Full HD 1920 x 1080

CONNECTIVITY, SPEAKER



HDMI x 2 **VGA**



Built-In Stereo Speakers 8W + 8W

VIEW ANGLE, VESA



178° Ultra-Wide Viewing Angle



VESA Wall-Mountable

OTHER FEATURES



Media Player MEDIA PLAYER



High Contrast



Remote Control




Video Modes


HANNspree

Experts in **Display**

Display Size	100,33 cm / 39,5" Diagonal	
Panel Type	TFT – LED Backlight VA Panel (*)	
Aspect Ratio	16:9	
Resolution (H x V)	1920 x 1080 Full HD	
Brightness	300cd/m² (Typical)	
Contrast	5000:1 (Typical)	
Viewing Angle L/R; U/D	178° H / 178° V (CR >10)	
Response Time	9,5 msec (Typical)	
Pixel Pitch	0,45735 (H) x 0,4494 (V) mm	
Panel Surface	Glare, Haze-level 1%; Hard Coating 3H	
Display Colors	16.7M Colors	
Horizontal Frequency	30 ~ 83 kHz	
Vertical Frequency	56 ~ 75 Hz	
Max Display Frequency	1920 x 1080 @ 60Hz	
Input 1	VGA (D-Sub)	
Input 2	HDMI 1.4 x 2	
Input 3	USB 2.0 x 2 (5V 0.5A Output) Media Player	
Input 4	Audio In	
Buil-in Speakers	Yes, 2 x 8W, 8Ω; Earphone Jack	
Power Consumption	On: 29W; Stand-by: 0,5W; Off: ≤0,3W	
AC Power Range	AC 100 ~ 240 Volt; 50 ~ 60 Hz	
Product Dimensions	906,9 x 206,8 x 567,7mm with stand (W x D x H) 906,9 x 82,9 x 519 mm without stand (W x D x H)	
Packing Dimensions	990 x 140 x 640 mm (W x D x H)	
Net / Gross Weight	5,2 Kg / 7,6 Kg	

VESA Mounting	200 x 200 mm	
Monitor Stand	Fixed Stand	
Tilt / Kensington Lock	-/-	
Pivot / Swivel	-/-	
Controls	Power, VOL+, VOL-, CH+, CH-, SOURCE, MENU	
Color	Normal, Warm, Standard, Cool Mode	
Features	Auto Power ON Auto Playback (Photo and Video) Standby-Wake up on HDMI Signal HDMI CEC Function Max. non-stop operating time: 12/7 Suitable for both landscape and portrait installations	
On Screen Display	7 OSD Languages	
Accessory	Power Cable not removable (1,8m); HDMI Cable (1,5m): Remote Control; Warranty Card; Quick Start Guide	
	Supplier's Name HANNspree	





Supplier's Name	HANNspree
Model Name	HL400UPB
Energy efficiency class for standard Dynamic Range (SDR)	D
Annual Energy Power Consumption (kWh/1000h)	29 kWh/1000h
On mode power demand for Standard Dynamic Range (SDR)	29 W
Off mode power demand (W)	n.a.
Standby mode power demand (W)	0,5 W
Screen Diagonal (cm / inches)	100,33cm/39,5"
Resolution	1920 x 1080

PART NO.: HL400UPB



^{* &}quot;VA" word mark / trademark and related patents on technologies belong to their respective owners.



^{© 2022} HANNSpree Europe Holdings B.V. Specifications and design as well as accessories are subject to change without notice. Screen shots are simulated. Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local HANNspree authorized representatives for the availability of specific products in your area. All brand, product, Service names and logos are trademarks and/or registered trademarks of their respective manufactures and Companies.